



NM Afterglow 257 is a solventfree epoxy-based afterglowing product. Afterglowing products are mainly used as guidelines for escape-routes. The product can be applied as lines, dots or direction arrows.

To achieve full afterglowing effect, NM Afterglow 257 should be applied on a white primer coat. For this purpose, NM 70 Express in colour 27 is commonly used. Concrete surfaces should first be primed with NM Grundering BP 50 Super. NM 70 Express should be applied by brush or roller.

NM Afterglow 257 should be applied with a brush or a roller.

### Typical applications

- Afterglowing lines on concrete.

### Typical properties

**Resin:**

NM Efterlys 257

**Hardener:**

NM Härdare 255

**Mixing ratio:**

Resin-Hardener 100-25 by weight

<i>Density:</i>	1269 kg/m <sup>3</sup>
<i>Potlife 100g 20°C:</i>	30 minutes
<i>Afterglowing time:</i>	>60 minutes
<i>Colour:</i>	Yellowish green.
<i>Consumption:</i>	approx. 0.6 kg/m <sup>2</sup> (Approx. 10 meters of marking)
<i>Chemical resistance:</i>	See Floor 80
<i>Normal packing:</i>	1.0+0.25=1.25 kg
<i>Cleaning solvent:</i>	Acetone