



NM Afterglow 258 is a flexible solventfree epoxybased afterglowing product. Afterglowing products are mainly used as guidelines for escape-routes. The product can be applied as lines, dots or direction arrows.

NM Afterglow 258 is specially designed for soft surfaces like PVC or linoleumcarpets.

To achieve full afterglowing effect, NMAfterglow 258 should be applied on a white primer coat. For this purpose, NM 70 Express in colour 27 is commonly used.

All surfaces should be sound and free from oil, grease and dust and be dry during application.

NM Afterglow 258 should be applied with a brush.

Typical properties

Resin:

NM Efterlys 258

Hardener:

NM Härdare 259

Mixing ratio:

Resin-Hardener 100-40 by weight

<i>Density:</i>	1269 kg/m ³
<i>Potlife 100g 20°C:</i>	30 minutes
<i>Afterglowing time:</i>	>60 minutes
<i>Colour:</i>	Yellowish green.
<i>Consumption:</i>	approx. 0.6 kg/m ² (Approx. 10 meters of marking)
<i>Chemical resistance:</i>	See Floor 80
<i>Normal packing:</i>	1.0 + 0.4 = 1.4 kg
<i>Cleaning solvent:</i>	Acetone

Typical applications

- Afterglowing lines on soft surfaces like PVC or Linoleum.