



NM 40 Elite is a solvent free epoxy topcoat designed for decorative heavy duty floors build up of NM 400 Elite.

NM 40 Elite has been developed to give optimal wetting to the substrate and give's a one coloured surface free of pores.

NM 40 Elite fullfills all demands as topcoat according to free of pores, sealing and cleanability

The coating is applied with a squeegee and is pre-rolled with a felt or mohair roller.

### Typical applications

- Topcoat for decorative heavy duty floors.

### Typical properties

**Resin:**

NM Golv 40 Elit

**Hardener:**

NM Härdare 400

**Mixing ratio:**

Resin-Hardener 100-25 by weight

<i>Density:</i>	1375 kg/m <sup>3</sup>
<i>Viscosity at 25°C:</i>	400 mPa·s
<i>Solid-content:</i>	100%
<i>Potlife 100g 20°C:</i>	35 minutes
<i>Compressive strength:</i>	98 MPa
<i>Tensile strength:</i>	30 MPa
<i>Flexural strenght:</i>	49 MPa
<i>E-modulus:</i>	9 GPa
<i>Chemical resistance:</i>	see NM 400Elite
<i>Minimum curing temp:</i>	+ 10°C
<i>Colour:</i>	See colour cart
<i>Consumption:</i>	~0.8 kg/m <sup>2</sup>
<i>Normal packing:</i>	4.0+1.0 +5.0 kg
<i>Cleaning solvent:</i>	Acetone